

# Recirculation loader

## STANDARD FEATURES

- ※ SOLid and stable design;
- ※ Stable and reliable integrated control system;
- ※ Light touch LED membrane switch or touch S C r e e n control panel options available;
- ※ Uninterrupted loading,
- ※ Smooth and parallel width adjustment;
- ※ Pressure regulated 0 n pusher's tO prevent board damage;
- ※ Small machine footprint;
- ※ Machine always fault monitoring;
- ※ SMEMAcompatible.

## TECHNICAL SPECIFICATIONS

Model No	TN-BLW250	TN-BLW350	TN-BLW460
PCB LxW (Min~Max)	(60x60)~(350x250)	(60x60)~(450x350)	(60x60)~(500x460)
Machine /Wooden pack (LxWxH)	490x520x1600/510x600x1800	490x620x1600/510x720x1800	600x750x1600/710x850x1800
Machine/packed weight	120kg/140kg	120kg/140kg	120kg/140kg

function	Maximum PCB capacity	PCB loading time	Power supply
This unit is used for loading PCB.	50pcs	Approx 6seconds	100-230VAC(customized), 1ph,max150VA
Transport height	Transport direction	PCB thickness	Step pitches select
950 ±20mm (or customized)	Left to right / right to left(optional)	Min 0.6mm	10mm, 20mm, 30mm, 40mm